

APPLICATION FOR

UNITED STATES LETTERS PATENT

S P E C I F I C A T I O N

Inventors: Ryusuke YAMAGUCHI

Shoichi NAGATOMO

## A PORTABLE IMAGE CAPTURING DEVICE

## BACKGROUND OF THE INVENTION

5

## FIELD OF THE INVENTION

The present invention relates to a portable image capturing device which has an optical communication function, e.g., infrared communication or the like, and an image capturing function, e.g., a digital camera or the like.

## DESCRIPTION OF THE PRIOR ART

An optical communication technique which carries out data communication with an external device by using light signal is known.

In the electronic apparatus having such a function, there is a portable electronic apparatus, e.g., a PDA or a digital still camera, having the infrared communication function, to convert data to infrared ray signal and to carry out data communication with the external device by using the signal, as one of optical communication. Such a portable electronic apparatus comprises an infrared ray emitting element having an infrared-emitting diode and the like, for sending infrared ray signal, and an infrared detecting element having a photodiode and the like for receiving the infrared ray signal, as a construction to realize the infrared communication function.

In a portable electronic apparatus having the infrared

communication function, in order to carry out data communication with an external electronic device, e.g., a PC or the like, an infrared communication window comprising transparent parts is formed in a case body, and a cover for  
 5 infrared communication, which is made by forming an optical filter material is provided on the window, to cover the infrared ray emitting element and the infrared detecting element which are provided inside.

The cover for infrared communication cuts the wavelengths  
 10 contributing to interruptions for communication during infrared communication, to improve the reliability of data.

In such a portable electronic apparatus having the infrared communication function, in particular, in a capturing device, e.g., digital camera or the like, it is required to  
 15 provide an infrared communication portion and a camera unit individually. However, it is difficult to arrange the infrared communication portion and the camera unit individually to each other because of ensuring a good portability. Therefore, it is supposed that the problems of inconvenience of user's  
 20 handling the portable electronic apparatus, e.g., on confirmation of captured images, transmission of capturing image data to an external device, or the like.

25

## SUMMARY OF THE INVENTION

An object of the invention is to provide a portable image

capturing device which has an optical communication function, in particular, an infrared communication function, and an image capturing function and which improves the convenience on user's handling.

5 Another object of the invention is to reduce the number of necessary components and the number of steps for assembling by covering both the image capturing portion (camera portion) and the optical communication portion (infrared communication portion) in common by a transparent covering member.

10 The present invention was developed in order to solve the above-described problems. In accordance with one aspect of the present invention, the portable image capturing device, comprises: a device body, an image capturing portion (camera portion) and an optical communication portion (infrared communication portion), which are provided on the device body, and a transparent covering member for covering both the image capturing portion and the optical communication portion, which is provided on the device body.

20 According to the present invention, because the image capturing portion and an optical communication are provided adjacent to each other on the device body, it is possible to improve the convenience on user's handling and to reduce the number of necessary components and the number of steps for assembling by covering both the image capturing portion and the optical communication portion in common by a transparent covering member.

25

## BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 is a plan view showing the entirety of a portable  
 5 image capturing device, as an embodiment of the invention;

FIG. 2 is an enlarged plan view of the device body shown  
 in FIG. 1;

FIG. 3 is a perspective view of the device body shown in  
 FIG. 2;

10 FIG. 4 is a front view showing the camera portion and the  
 optical communication portion (infrared communication  
 portion) in the device body shown in FIG. 3;

FIG. 5 is a side view of the device body shown in FIG.  
 4;

15 FIG. 6 is a perspective view of only the device body shown  
 in FIG. 3, from the side opposite to the camera portion (image  
 capturing portion) and the optical communication portion  
 (infrared communication portion) at an angle;

FIG. 7 is a bottom view of the body portion of the device  
 20 shown in FIG. 6, in which the camera portion and the optical  
 communication portion (infrared communication portion) are  
 shown in cross section and the inner module is shown without  
 the case back;

FIG. 8 is a cross-sectional view taken on line A-A of FIG.  
 25 7;

FIG. 9 is a cross-sectional view taken on line B-B of FIG.  
 7;

FIG. 10 is an exploded perspective view showing the cover structure of the camera portion and the optical communication portion (infrared communication portion), which are shown in FIG. 4;

5        FIG. 11 is a bottom view of the device body shown in FIG. 6;

FIG. 12 is an exploded perspective view showing the case back, the ring for waterproof, and the battery cover, which are attached to the rear surface of the device body shown in FIG.

10    1;

FIG. 13 is an enlarged perspective view showing the structure of the rear side of the battery cover shown in FIG. 12;

15    FIG. 14 is an exploded perspective view showing the case back shown in FIG. 12;

FIG. 15 is a cross-sectional view taken on line C-C of FIG. 14;

FIG. 16 is a rear view of the case back shown in FIG. 14;

20    FIG. 17 is an enlarged cross-sectional view taken on line D-D of FIG. 16;

FIG. 18A is a front view showing the structure of the battery cover shown in FIG. 13, and FIG. 18B is a rear view thereof;

25    FIG. 19 is a cross-sectional view taken on line E-E of FIG. 18B;

FIG. 20 is an enlarged side view of the "F" portion of FIG. 19;

FIGS. 21A and 21B show the attachment relationship between the battery cover and the case back, from the rear side, in which FIG. 21A is a view when inserting the battery cover into the case back, and FIG. 21B is a view when rotating the battery cover to lock to the case back;

FIG. 22 is an exploded perspective view showing the cover structure of the camera portion and the optical communication portion (infrared communication portion), as the second embodiment of the invention;

FIG. 23 is an exploded perspective view showing the cover structure of the camera portion and the optical communication portion (infrared communication portion), as the third embodiment of the invention;

FIG. 24 is a bottom view of the device body shown in FIG. 23, in which the camera portion and the optical communication portion (infrared communication portion) are shown in cross section;

FIG. 25 is a cross-sectional view taken on line C-C of FIG. 24;

FIG. 26 is an exploded perspective view showing the cover structure of the camera portion and the optical communication portion (infrared communication portion), as the fourth embodiment of the invention;

FIG. 27 is a bottom view of the device body shown in FIG. 26, in which the camera portion and the optical communication portion (infrared communication portion) are shown in cross section;

FIG. 28 is a cross-sectional view taken on line D-D of FIG. 27;

FIG. 29 is a cross-sectional view taken on line E-E of FIG. 27;

5 FIG. 30 is an exploded perspective view showing the cover structure of the camera portion and the optical communication portion (infrared communication portion), as the fifth embodiment of the invention;

10 FIG. 31 is a bottom view of the device body shown in FIG. 30, in which the camera portion and the optical communication portion (infrared communication portion) are shown in cross section;

FIG. 32 is an enlarged plan view of the device body, as the sixth embodiment of the invention;

15 FIG. 33 is an exploded perspective view showing the relationship between the device body shown in FIG. 32 and another infrared communication apparatus;

FIG. 34 is an enlarged plan view of the device body, as the seventh embodiment of the invention; and

20 FIG. 35 is a perspective view of the device body shown in FIG. 34.

## DETAILED DESCRIPTION OF THE INVENTION

25

### FIRST EMBODIMENT

The first embodiment of the invention will be explained



in detail with reference to the drawings.

FIG. 1 is a plan view showing the entirety of a portable image capturing device, as an embodiment of the invention, in which the reference numeral 1 denotes a wrist watch (portable image capturing device), the numeral 2 denotes a case body (device body), the numerals 3 and 4 denote a pair of wrist bands, and the numeral 5 denotes a loop (band fastening member).

FIG. 2 is an enlarged plan view of the portion of the case body 2, FIG. 3 is a perspective view of the portion of the case body 2, FIG. 4 is a front view showing the camera portion (image capturing portion) and the optical communication portion in the portion of the case body 2, FIG. 5 is a side view of the portion of the case body 2, and FIG. 6 is a perspective view of only the portion of the case body 2, from the side opposite to the camera portion and the optical communication portion at an angle. In these figures, the reference numeral 6 denotes an image capturing lens (camera portion), the numeral 7 denotes an infrared communication portion (optical communication portion), the numeral 8 denotes a case back, the numeral 9 denotes a battery cover, the numeral 21 denotes a transparent covering member, the numeral 22 denotes a data display portion, the numeral 23 denotes a shutter button (shutter operating member), the numeral 24 denotes an adjustment key, the numeral 25 denotes a mode key, the numeral 26 denotes a reverse key, the numeral 27 denotes a display changing key, the numeral 28 denotes a forward key, and the numeral 29 denotes a bezel.

The case body 2 of the wrist watch 1 which is an application

example of the portable image capturing device according to the invention has an end side surface at which a wrist band 3 is attached in the other side of the case body, in FIGS. 1 and 2. In the end side surface, the image capturing lens 6 which is  
 5 the camera portion and the infrared communication portion 7 which is the optical communication portion are provided near to each other in parallel, as shown in FIGS. 3 and 4.

In the case body 2, the transparent covering member 21 which covers the image capturing lens 6 and the infrared  
 10 communication portion 7 is provided on the end side surface, and the data display portion and the shutter button 23 are provided on the upper surface. The shutter button 23 is positioned in the opposite side to the image capturing lens 6 and the infrared communication portion 7 with respect to the  
 15 data display portion 22. Shutter operation can be carried out by pushing the shutter button 23 toward the rear surface from the front surface in FIG. 3.

In a side surface of the case body 2, the adjustment key 24 and the mode key 25 are provided. In the other side surface  
 20 of the case body 2, the reverse key 26, the display changing key 27, and the forward key 28 are provided. The reverse key 26 and the display changing key 27 are for making the data display portion 22 display a plurality of stored images and change them.

On the rear surface of the case body 2 near the transparent  
 25 covering member 21, a pair of projecting band attachment portions 201 and 201 for attaching the wrist band 3 in the side of the image capturing lens 6 and the infrared communication

portion 7 are provided, as shown in FIGS. 3-6. Between the pair of projecting band attachment portions 201 and 201, a band attachment bar 203 is attached. Therefore, the wrist band 3 attached to the band attachment bar 203 can be rotated on the attachment bar 203 to be overlapped on the rear surface of the case body 2, as shown by a line for supposition (two-dot chain line) in FIG. 5.

On the upper surface of the case body 2, the bezel 29 is assembled for shock resistance. To the rear surface of the case body 2, the case back 8 is locked securely by screws. To the central portion of the case back 8, the battery cover 9 is attached, as described later.

The attachment position of the band attachment bar 203 may be positioned in the rear surface side than the battery cover 9.

FIG. 7 is a bottom view showing the inner module in the case body 2 without the case back, in which the main portion is shown in cross section, FIG. 8 is a cross-sectional view taken on line A-A of FIG. 7, FIG. 9 is a cross-sectional view taken on line B-B of FIG. 7, and FIG. 10 is an exploded perspective view showing the cover structure of the image capturing lens 6 and the infrared communication portion 7. In these figures, the reference numeral 11 denotes a module, the numeral 12 denotes a board, the numerals 13 and 14 denote housings, the numeral 15 denotes a circuit supporter, the numeral 16 denotes a connector socket, the numeral 17 denotes a battery insertion portion, the numerals 61 denote solder balls (electric

conductive member), the numeral 62 denotes an electrode film, the numeral 63 denotes a connector, the numeral 71 denotes an infrared emitting element, the numeral 72 denotes an infrared detecting element, the numeral 73 denotes a cover for infrared communication (filter member), and the numerals 89 and 99 denote O-rings (water proof members).

The module 11 has functions of watch, transmission and data display. The module 11 comprises the board 12 which has a various types of electronic components mounted thereon, the housings 13 and 14 provided in both sides thereof, the circuit supporter 15 provided in the rear side of the board 12, and the like. In a cut-out portion at a corner of the module 11, a connector socket 16 is provided, and at a central portion of the circuit supporter 15, the battery insertion portion 17 is provided.

The image capturing lens 6 is fitted into a capturing window 206 of the case body 2. The infrared communication portion 7 is disposed in a communication window 207 of the case body 2. The transparent covering member 21 is attached into a recess portion 205 for cover attachment, which opens in the end side surface of the case body 2, to cover both the image capturing lens 6 and the infrared communication portion 7.

In the image capturing lens 6, a CMOS (Complementary Metal-Oxide Semiconductor) for data conversion of signals from the infrared detecting element and for transfer thereof is installed. The electrode film 62 is connected with the image capturing lens 6 through many solder balls 61 which are the

electric conductive member. The electrode film 62 is provided with a connector 63 at the end thereof.

5 The image capturing lens 6 is fitted in the capturing window 206 of the case body 2 before incorporating the module 11 into the case body.

10 The infrared communication portion 7 comprises the infrared emitting element 71 and the infrared detecting element 72, which are attached to the module 11. The module 11 is incorporated into the case body 2 so that the infrared emitting element 71 and the infrared detecting element 72 which make a pair are inserted into the communication window 207 of the case body 2.

15 After the connector 63 attached to the end of the electrode film 62 is fitted and connected to the connector socket 16 of the module 11, the case back 8 is locked securely by screws to the rear surface of the case body 2. Between the case body 2 and the case back 8, the O-ring (water proof ring) 89 is sandwiched and between the case back 8 and the battery cover 9, the O-ring (water proof ring) 99 is sandwiched.

20 Then, the periphery of the cover 73 for infrared communication which is a filter member is melted and fixed to the periphery of the communication window 207, as shown in FIG. 10. Further, the periphery of the transparent covering member 21 having a convex lens shape is melted and fixed to the periphery 25 of the recess portion 205 for cover attachment, to cover both the image capturing lens 6 and the infrared communication portion 7.

The transparent covering member 21 has a circular recess portion 211 on the front surface at a position corresponding to that of the image capturing lens 6. On the rear surface of the transparent covering member 21, a black printed layer 212 is formed at the portion except ones corresponding to the capturing window 206 and the communication window 207.

The shutter button 23 is provided to be slidable on a switch pin 231(not shown) without slipping out from the switch pin, as shown in FIG. 9. The switch pin 231 is provided to be slidable on the case body 2 without slipping out from the case body. Around the switch pin 231, a compressed coil screw 232 (not shown) is provided between the shutter button 23 and the case body 2.

When pressing down the shutter button 23 against the biasing force of the compressed coil screw 232 and thereby pressing down the switch pin 231, the top end of the switch pin 231 is brought into contact with an electrode with a shape like teeth of a comb on the board 12. As a result, the shutter switch is changed to on to open the shutter of camera.

The shutter button 23 is biased by a compressed coil screw 233 which is disposed between the shutter button and the case body 2, in the projecting direction of the compressed coil screw at both ends thereof, as shown in FIGS. 8 and 9. Thus, the shutter button 23 is supported stably.

As described above, according to the embodiment of the invention, because the image capturing lens 6 and the infrared communication portion 7 are provided near to each other in

parallel, in the end side surface of the wristwatch 1, it is possible to capturing an image by pressing down the shutter button 23 which is arranged in this side and also to communicate data, while putting it on an arm and using the data display portion 22 as a monitor, i.e., a finder.

Because the portable electronic apparatus of the embodiment can be used in a state of placing the case body 2 on a stable table or the like, with overlapping the wrist band 3 on the rear surface of the case body 2, as shown by the two-dot chain line in FIG. 5, it is possible to capturing an image and to communicate data, in a state of placing the case body 2 on an appropriate stable place and directing it in an appropriate direction.

Because both the image capturing lens 6 and the infrared communication portion 7 are covered by a transparent covering member 21, it is possible to reduce the number of necessary components and the number of steps for assembling.

Further, because the transparent covering member 21 with a convex lens shape has a circular recess portion 211 on the front surface at a position corresponding to that of the image capturing lens 6 and has a black printed layer 212 on the rear surface thereof at portions except ones corresponding to the capturing window 206 and the communication window 207, it does not interfere optically with capturing images through the image capturing lens 6 nor exert an adverse optical influence upon the image capturing lens 6 and the infrared communication portion, e.g., interference of optical axes to each other.

The circular recess portion 211 of the transparent covering member 21 may have a lens structure. No cover 73 for infrared communication may be provided by making the transparent covering member 21 by a filter member and by  
 5 reducing the filter property by the circular recess portion 211.

FIG. 11 is a bottom view of the case body 2 of the apparatus, and FIG. 12 is an exploded perspective view showing the case back 8, the O-ring 99 for waterproof, and the battery cover 9, which are attached to the rear surface of the case body 2 of the  
 10 apparatus.

In the case back 8, an attachment hole 80 through which a battery can be attached is formed at the central portion, and a loop groove 81 for receiving a waterproof ring is formed in the surface around the attachment hole 80, as also shown in FIGS.  
 15 14 to 16. In the periphery of the attachment hole 80, a pair of flanges 82 and 82 which are faced to each other in a radial direction to have a smaller diameter. Each of the flanges 82 is formed at an approximate angle of 90°. At an end in one direction of each flange 82, a small cut-out 83 is formed.

In the loop groove 81 for receiving a waterproof ring of the case back 8, the O-ring 99 is fitted. The case back 8 is fixed to the rear surface of the case body 2 at four corners by using screws 84, as shown in FIG. 11. Between the case body 2 and the case back 8, the O-ring 99 is provided, as shown in  
 20 FIGS. 8 and 9.

As shown in FIGS. 13, 18 and 19, in the front surface of the battery cover 9, a radial direction recess 90 which extends



radially to pass through the center is formed, and in the rear surface thereof, a fitting portion 91 having a shape corresponding to the attachment hole 80 is provided. At the central portion of the fitting portion 91, a battery clamp 95 which comprises a pair of plate springs facing to each other is attached.

On the periphery of the fitting portion 91, a pair of small diameter portions 92 and 92 are formed radially to have a shape fitting in the pair of flanges 82 and 82 of the case back 8, and a pair of large diameter portions are formed radially next to the small diameter portions 92 and 92. Between each large diameter portion and the front surface of the battery cover 9, a circumferential groove 93 with a diameter which can receive the small diameter flange 82 of the case back 8 and is closed at the bottom end. In the middle of each large diameter portion, a small projection 94 is formed toward the circumferential groove 93 at a position corresponding to that of the small cut-out 83 when rotating to insert the small diameter flange 82 into the circumferential groove 93 to the bottom.

FIGS. 21A and 21B show the attachment relationship between the battery cover 9 and the case back 8, from the rear side, in which FIG. 21A is a view when inserting the battery cover 9 into the case back 8, and FIG. 21B is a view when rotating the battery cover 9 to lock to the case back 8.

In order to fix the battery cover 9 to the case back 8, the fitting portion 91 of the battery cover 9 is inserted into the attachment hole 80 of the case back 8, with fitting the small

diameter portions 92 and 92 into the small diameter flanges 82 of the case back 8.

Thereafter, the battery cover 9 is rotated in the direction of the arrow in FIG. 21A (from the operator's point of view, in the clockwise direction) by inserting a coin into the radial direction recess 90 to rotate it. Then, the small diameter flanges 82 of the case back 8 are being inserted into the circumferential groove 93 of the battery cover 9 while the O-ring 99 in the loop groove 81 is being compressed against the peripheral rear surface of the battery cover 9.

When the small projections 94 in the circumferential grooves 93 reach the positions of the small cut-outs 83 in the flanges 82 of the case back 8, the operator can know the fact that the battery cover 9 has reached the rotational fixation position, by a click feeling.

In order to take the battery cover 9 off the case back 8, it may reverse the order of steps.

## SECOND EMBODIMENT

The second embodiment is different from the first embodiment in the following points.

In the portable image capturing device according to the second embodiment, the cover 73 for an infrared communication in the first embodiment is not used, a transparent covering member 121 having an infrared filtering property is adopted, as shown by oblique lines in FIG. 22. The circular recess portion 211 provided on the surface of the transparent covering

member 121 is formed to be thin than the rest portion, thereby it functions to reduce the infrared filtering property. In figures, the same numbers are attached to structural members, elements, portions or the like corresponding to those of the first embodiment. A detailed explanation for such corresponding structural members, elements, portions or the like is omitted.

According to use of the transparent covering member 121 having an infrared filtering property, it is possible to reduce the number of necessary parts because the cover 73 for an infrared communication used in the first embodiment is not required.

### THIRD EMBODIMENT

The third embodiment is different from the first embodiment in the following points. In the portable image capturing device according to the third embodiment, the cover 73 for an infrared communication in the first embodiment is not used, an infrared filtering seal 173 which is shown by oblique lines in FIG. 23, is adhered to the periphery of the front surface of the communication window 207 of the recess portion 205 for cover attachment, as shown in FIGS. 23 to 25. In the figures, the same numbers are attached to structural members, elements, portions or the like corresponding to those of the first embodiment. A detailed explanation for such corresponding structural members, elements, portions or the like is omitted.

According to use of the infrared filtering seal 173

adhered, without the cover 73 for an infrared communication used in the first embodiment, it is possible to mount parts with high density and to make the portable image capturing device small-sized.

5

#### FOURTH EMBODIMENT

The fourth embodiment is different from the first embodiment in the following points. In the portable image capturing device according to the fourth embodiment, the cover 10 73 for an infrared communication in the first embodiment is not used, a transparent covering member 221 which has an infrared filter characteristic form portion 2210 (the range of which is shown by oblique lines in FIG. 26) in the side of the communication window 207 is adopted instead thereof. The 15 transparent covering member 221 is produced by the two-color forming is used. In the figures, the same numbers are attached to structural members, elements, portions or the like corresponding to those of the first embodiment. A detailed explanation for such corresponding structural members, 20 elements, portions or the like is omitted.

Because the side of the communication window 207 is covered by the infrared filter characteristic form portion 2210 of the transparent covering member 221 produced by the two-color forming, it is possible to reduce the number of necessary 25 parts because the cover 73 for an infrared communication used in the first embodiment is not required.

## FIFTH EMBODIMENT

The fifth embodiment is different from the first embodiment in the following points. In the portable image capturing device according to the fifth embodiment, the black printed layer 212 in the first embodiment is not used, a rib 208 processed for positioning the transparent covering member 321 is disposed between the capturing window 206 of the recess portion 205 for cover attachment and the communication window 207, as shown in FIGS. 30 and 31. The rib 208 also plays a role to prevent the image capturing lens 6 and the infrared communication portion 7 from being adversely affected optically. In the transparent covering member 321, a recess portion 322 corresponding to the rib 208 is formed. In the figures, the same numbers are attached to structural members, elements, portions or the like corresponding to those of the first embodiment. A detailed explanation for such corresponding structural members, elements, portions or the like is omitted.

In this embodiment, because the black printed layer 212 in the first embodiment is not used and the recess portion 322 of the transparent covering member 321 is fitted to the rib 208 which is disposed between the capturing window 206 of the recess portion 205 for cover attachment and the communication window 207, it is possible to prevent the transparent covering member 321 from slipping off by shock. Such a structure make easy to assemble the transparent covering member 321 to the device body 2.

## SIXTH EMBODIMENT

The sixth embodiment is different from the first embodiment in the following points. In the portable image capturing device according to the sixth embodiment, the image capturing portion and the infrared communication portion 701 are disposed in the device body (200) so that the camera direction for taking a photograph (Y-axis direction in FIGS. 32 and 33) by the image capturing lens 6 is approximately perpendicular to the infrared communication direction (X-axis direction in the figures) by the infrared communication portion 701. The side surfaces perpendicular to each other having the image capturing lens 6 and the infrared communication portion 701 are covered with a single transparent covering member 421. In FIG. 33, the reference numeral 702 denotes an apparatus for infrared communication, e.g., an infrared communication port apparatus which is connected to a PC. In the figures, the same numbers are attached to structural members, elements, portions or the like corresponding to those of the first embodiment. A detailed explanation for such corresponding structural members, elements, portions or the like is omitted.

According to this embodiment, because the camera direction for taking a photograph is approximately perpendicular to the infrared communication direction, in addition to the advantageous effects according to the first embodiment, it is possible to handle the device easily even in a condition of wearing the device on an arm while transmitting data by infrared communication, and to enable camera handling

to take a photograph by remote control (using infrared ray).

#### SEVENTH EMBODIMENT

The seventh embodiment is different from the first  
 5 embodiment in the following points. In the portable image  
 capturing device according to the seventh embodiment, the  
 device body 250 comprises a single transparent covering member  
 521 which covers both the data display portion (LCD) 521 and  
 the side surface having the image capturing lens 6 and the  
 10 infrared communication portion 7. In FIG. 34, the numeral 522  
 denotes a display window. In FIG. 35, the numeral 529 denotes  
 a bezel. In the figures, the same numbers are attached to  
 structural members, elements, portions or the like  
 corresponding to those of the first embodiment. A detailed  
 15 explanation for such corresponding structural members,  
 elements, portions or the like is omitted.

According to the embodiment, because a single transparent  
 covering member 521 which covers both the data display portion  
 (LCD) 521 and the side surface is provided, it is possible to  
 20 reduce the number of necessary parts.

Although the apparatus of the invention is applied to a  
 watch in the above-described embodiment, it is not limited to  
 this, and the invention can be applied to any portable  
 25 electronic apparatus (portable image capturing device), e.g.,  
 a portable terminal and the like.

Also the structure or the like for the camera portion

(image capturing portion) and the optical communication portion (infrared communication portion) are not limited to that of the embodiment. It is of course that other concrete detailed structures or the like of the apparatus of the invention may  
 5 be changed appropriately.

1000  
 1001  
 1002  
 1003  
 1004  
 1005  
 1006  
 1007  
 1008  
 1009  
 1010  
 1011  
 1012  
 1013  
 1014  
 1015  
 1016  
 1017  
 1018  
 1019  
 1020  
 1021  
 1022  
 1023  
 1024  
 1025  
 1026  
 1027  
 1028  
 1029  
 1030  
 1031  
 1032  
 1033  
 1034  
 1035  
 1036  
 1037  
 1038  
 1039  
 1040  
 1041  
 1042  
 1043  
 1044  
 1045  
 1046  
 1047  
 1048  
 1049  
 1050  
 1051  
 1052  
 1053  
 1054  
 1055  
 1056  
 1057  
 1058  
 1059  
 1060  
 1061  
 1062  
 1063  
 1064  
 1065  
 1066  
 1067  
 1068  
 1069  
 1070  
 1071  
 1072  
 1073  
 1074  
 1075  
 1076  
 1077  
 1078  
 1079  
 1080  
 1081  
 1082  
 1083  
 1084  
 1085  
 1086  
 1087  
 1088  
 1089  
 1090  
 1091  
 1092  
 1093  
 1094  
 1095  
 1096  
 1097  
 1098  
 1099  
 1100  
 1101  
 1102  
 1103  
 1104  
 1105  
 1106  
 1107  
 1108  
 1109  
 1110  
 1111  
 1112  
 1113  
 1114  
 1115  
 1116  
 1117  
 1118  
 1119  
 1120  
 1121  
 1122  
 1123  
 1124  
 1125  
 1126  
 1127  
 1128  
 1129  
 1130  
 1131  
 1132  
 1133  
 1134  
 1135  
 1136  
 1137  
 1138  
 1139  
 1140  
 1141  
 1142  
 1143  
 1144  
 1145  
 1146  
 1147  
 1148  
 1149  
 1150  
 1151  
 1152  
 1153  
 1154  
 1155  
 1156  
 1157  
 1158  
 1159  
 1160  
 1161  
 1162  
 1163  
 1164  
 1165  
 1166  
 1167  
 1168  
 1169  
 1170  
 1171  
 1172  
 1173  
 1174  
 1175  
 1176  
 1177  
 1178  
 1179  
 1180  
 1181  
 1182  
 1183  
 1184  
 1185  
 1186  
 1187  
 1188  
 1189  
 1190  
 1191  
 1192  
 1193  
 1194  
 1195  
 1196  
 1197  
 1198  
 1199  
 1200  
 1201  
 1202  
 1203  
 1204  
 1205  
 1206  
 1207  
 1208  
 1209  
 1210  
 1211  
 1212  
 1213  
 1214  
 1215  
 1216  
 1217  
 1218  
 1219  
 1220  
 1221  
 1222  
 1223  
 1224  
 1225  
 1226  
 1227  
 1228  
 1229  
 1230  
 1231  
 1232  
 1233  
 1234  
 1235  
 1236  
 1237  
 1238  
 1239  
 1240  
 1241  
 1242  
 1243  
 1244  
 1245  
 1246  
 1247  
 1248  
 1249  
 1250  
 1251  
 1252  
 1253  
 1254  
 1255  
 1256  
 1257  
 1258  
 1259  
 1260  
 1261  
 1262  
 1263  
 1264  
 1265  
 1266  
 1267  
 1268  
 1269  
 1270  
 1271  
 1272  
 1273  
 1274  
 1275  
 1276  
 1277  
 1278  
 1279  
 1280  
 1281  
 1282  
 1283  
 1284  
 1285  
 1286  
 1287  
 1288  
 1289  
 1290  
 1291  
 1292  
 1293  
 1294  
 1295  
 1296  
 1297  
 1298  
 1299  
 1300  
 1301  
 1302  
 1303  
 1304  
 1305  
 1306  
 1307  
 1308  
 1309  
 1310  
 1311  
 1312  
 1313  
 1314  
 1315  
 1316  
 1317  
 1318  
 1319  
 1320  
 1321  
 1322  
 1323  
 1324  
 1325  
 1326  
 1327  
 1328  
 1329  
 1330  
 1331  
 1332  
 1333  
 1334  
 1335  
 1336  
 1337  
 1338  
 1339  
 1340  
 1341  
 1342  
 1343  
 1344  
 1345  
 1346  
 1347  
 1348  
 1349  
 1350  
 1351  
 1352  
 1353  
 1354  
 1355  
 1356  
 1357  
 1358  
 1359  
 1360  
 1361  
 1362  
 1363  
 1364  
 1365  
 1366  
 1367  
 1368  
 1369  
 1370  
 1371  
 1372  
 1373  
 1374  
 1375  
 1376  
 1377  
 1378  
 1379  
 1380  
 1381  
 1382  
 1383  
 1384  
 1385  
 1386  
 1387  
 1388  
 1389  
 1390  
 1391  
 1392  
 1393  
 1394  
 1395  
 1396  
 1397  
 1398  
 1399  
 1400  
 1401  
 1402  
 1403  
 1404  
 1405  
 1406  
 1407  
 1408  
 1409  
 1410  
 1411  
 1412  
 1413  
 1414  
 1415  
 1416  
 1417  
 1418  
 1419  
 1420  
 1421  
 1422  
 1423  
 1424  
 1425  
 1426  
 1427  
 1428  
 1429  
 1430  
 1431  
 1432  
 1433  
 1434  
 1435  
 1436  
 1437  
 1438  
 1439  
 1440  
 1441  
 1442  
 1443  
 1444  
 1445  
 1446  
 1447  
 1448  
 1449  
 1450  
 1451  
 1452  
 1453  
 1454  
 1455  
 1456  
 1457  
 1458  
 1459  
 1460  
 1461  
 1462  
 1463  
 1464  
 1465  
 1466  
 1467  
 1468  
 1469  
 1470  
 1471  
 1472  
 1473  
 1474  
 1475  
 1476  
 1477  
 1478  
 1479  
 1480  
 1481  
 1482  
 1483  
 1484  
 1485  
 1486  
 1487  
 1488  
 1489  
 1490  
 1491  
 1492  
 1493  
 1494  
 1495  
 1496  
 1497  
 1498  
 1499  
 1500  
 1501  
 1502  
 1503  
 1504  
 1505  
 1506  
 1507  
 1508  
 1509  
 1510  
 1511  
 1512  
 1513  
 1514  
 1515  
 1516  
 1517  
 1518  
 1519  
 1520  
 1521  
 1522  
 1523  
 1524  
 1525  
 1526  
 1527  
 1528  
 1529  
 1530  
 1531  
 1532  
 1533  
 1534  
 1535  
 1536  
 1537  
 1538  
 1539  
 1540  
 1541  
 1542  
 1543  
 1544  
 1545  
 1546  
 1547  
 1548  
 1549  
 1550  
 1551  
 1552  
 1553  
 1554  
 1555  
 1556  
 1557  
 1558  
 1559  
 1560  
 1561  
 1562  
 1563  
 1564  
 1565  
 1566  
 1567  
 1568  
 1569  
 1570  
 1571  
 1572  
 1573  
 1574  
 1575  
 1576  
 1577  
 1578  
 1579  
 1580  
 1581  
 1582  
 1583  
 1584  
 1585  
 1586  
 1587  
 1588  
 1589  
 1590  
 1591  
 1592  
 1593  
 1594  
 1595  
 1596  
 1597  
 1598  
 1599  
 1600  
 1601  
 1602  
 1603  
 1604  
 1605  
 1606  
 1607  
 1608  
 1609  
 1610  
 1611  
 1612  
 1613  
 1614  
 1615  
 1616  
 1617  
 1618  
 1619  
 1620  
 1621  
 1622  
 1623  
 1624  
 1625  
 1626  
 1627  
 1628  
 1629  
 1630  
 1631  
 1632  
 1633  
 1634  
 1635  
 1636  
 1637  
 1638  
 1639  
 1640  
 1641  
 1642  
 1643  
 1644  
 1645  
 1646  
 1647  
 1648  
 1649  
 1650  
 1651  
 1652  
 1653  
 1654  
 1655  
 1656  
 1657  
 1658  
 1659  
 1660  
 1661  
 1662  
 1663  
 1664  
 1665  
 1666  
 1667  
 1668  
 1669  
 1670  
 1671  
 1672  
 1673  
 1674  
 1675  
 1676  
 1677  
 1678  
 1679  
 1680  
 1681  
 1682  
 1683  
 1684  
 1685  
 1686  
 1687  
 1688  
 1689  
 1690  
 1691  
 1692  
 1693  
 1694  
 1695  
 1696  
 1697  
 1698  
 1699  
 1700  
 1701  
 1702  
 1703  
 1704  
 1705  
 1706  
 1707  
 1708  
 1709  
 1710  
 1711  
 1712  
 1713  
 1714  
 1715  
 1716  
 1717  
 1718  
 1719  
 1720  
 1721  
 1722  
 1723  
 1724  
 1725  
 1726  
 1727  
 1728  
 1729  
 1730  
 1731  
 1732  
 1733  
 1734  
 1735  
 1736  
 1737  
 1738  
 1739  
 1740  
 1741  
 1742  
 1743  
 1744  
 1745  
 1746  
 1747  
 1748  
 1749  
 1750  
 1751  
 1752  
 1753  
 1754  
 1755  
 1756  
 1757  
 1758  
 1759  
 1760  
 1761  
 1762  
 1763  
 1764  
 1765  
 1766  
 1767  
 1768  
 1769  
 1770  
 1771  
 1772  
 1773  
 1774  
 1775  
 1776  
 1777  
 1778  
 1779  
 1780  
 1781  
 1782  
 1783  
 1784  
 1785  
 1786  
 1787  
 1788  
 1789  
 1790  
 1791  
 1792  
 1793  
 1794  
 1795  
 1796  
 1797  
 1798  
 1799  
 1800  
 1801  
 1802  
 1803  
 1804  
 1805  
 1806  
 1807  
 1808  
 1809  
 1810  
 1811  
 1812  
 1813  
 1814  
 1815  
 1816  
 1817  
 1818  
 1819  
 1820  
 1821  
 1822  
 1823  
 1824  
 1825  
 1826  
 1827  
 1828  
 1829  
 1830  
 1831  
 1832  
 1833  
 1834  
 1835  
 1836  
 1837  
 1838  
 1839  
 1840  
 1841  
 1842  
 1843  
 1844  
 1845  
 1846  
 1847  
 1848  
 1849  
 1850  
 1851  
 1852  
 1853  
 1854  
 1855  
 1856  
 1857  
 1858  
 1859  
 1860  
 1861  
 1862  
 1863  
 1864  
 1865  
 1866  
 1867  
 1868  
 1869  
 1870  
 1871  
 1872  
 1873  
 1874  
 1875  
 1876  
 1877  
 1878  
 1879  
 1880  
 1881  
 1882  
 1883  
 1884  
 1885  
 1886  
 1887  
 1888  
 1889  
 1890  
 1891  
 1892  
 1893  
 1894  
 1895  
 1896  
 1897  
 1898  
 1899  
 1900  
 1901  
 1902  
 1903  
 1904  
 1905  
 1906  
 1907  
 1908  
 1909  
 1910  
 1911  
 1912  
 1913  
 1914  
 1915  
 1916  
 1917  
 1918  
 1919  
 1920  
 1921  
 1922  
 1923  
 1924  
 1925  
 1926  
 1927  
 1928  
 1929  
 1930  
 1931  
 1932  
 1933  
 1934  
 1935  
 1936  
 1937  
 1938  
 1939  
 1940  
 1941  
 1942  
 1943  
 1944  
 1945  
 1946  
 1947  
 1948  
 1949  
 1950  
 1951  
 1952  
 1953  
 1954  
 1955  
 1956  
 1957  
 1958  
 1959  
 1960  
 1961  
 1962  
 1963  
 1964  
 1965  
 1966  
 1967  
 1968  
 1969  
 1970  
 1971  
 1972  
 1973  
 1974  
 1975  
 1976  
 1977  
 1978  
 1979  
 1980  
 1981  
 1982  
 1983  
 1984  
 1985  
 1986  
 1987  
 1988  
 1989  
 1990  
 1991  
 1992  
 1993  
 1994  
 1995  
 1996  
 1997  
 1998  
 1999  
 2000  
 2001  
 2002  
 2003  
 2004  
 2005  
 2006  
 2007  
 2008  
 2009  
 2010  
 2011  
 2012  
 2013  
 2014  
 2015  
 2016  
 2017  
 2018  
 2019  
 2020  
 2021  
 2022  
 2023  
 2024  
 2025  
 2026  
 2027  
 2028  
 2029  
 2030  
 2031  
 2032  
 2033  
 2034  
 2035  
 2036  
 2037  
 2038  
 2039  
 2040  
 2041  
 2042  
 2043  
 2044  
 2045  
 2046  
 2047  
 2048  
 2049  
 2050  
 2051  
 2052  
 2053  
 2054  
 2055  
 2056  
 2057  
 2058  
 2059  
 2060  
 2061  
 2062  
 2063  
 2064  
 2065  
 2066  
 2067  
 2068  
 2069  
 2070  
 2071  
 2072  
 2073  
 2074  
 2075  
 2076  
 2077  
 2078  
 2079  
 2080  
 2081  
 2082  
 2083  
 2084  
 2085  
 2086  
 2087  
 2088  
 2089  
 2090  
 2091  
 2092  
 2093  
 2094  
 2095  
 2096  
 2097  
 2098  
 2099  
 2100  
 2101  
 2102  
 2103  
 2104  
 2105  
 2106  
 2107  
 2108  
 2109  
 2110  
 2111  
 2112  
 2113  
 2114  
 2115  
 2116  
 2117  
 2118  
 2119  
 2120  
 2121  
 2122  
 2123  
 2124  
 2125  
 2126  
 2127  
 2128  
 2129  
 2130  
 2131  
 2132  
 2133  
 2134  
 2135  
 2136  
 2137  
 2138  
 2139  
 2140  
 2141  
 2142  
 2143  
 2144  
 2145  
 2146  
 2147  
 2148  
 2149  
 2150  
 2151  
 2152  
 2153  
 2154  
 2155  
 2156  
 2157  
 2158  
 2159  
 2160  
 2161  
 2162  
 2163  
 2164  
 2165  
 2166  
 2167  
 2168  
 2169  
 2170  
 2171  
 2172  
 2173  
 2174  
 2175  
 2176  
 2177  
 2178  
 2179  
 2180  
 2181  
 2182  
 2183  
 2184  
 2185  
 2186  
 2187  
 2188  
 2189  
 2190  
 2191  
 2192  
 2193  
 2194  
 2195  
 2196  
 2197  
 2198  
 2199  
 2200  
 2201  
 2202  
 2203  
 2204  
 2205  
 2206  
 2207  
 2208  
 2209  
 2210  
 2211  
 2212  
 2213  
 2214  
 2215  
 2216  
 2217  
 2218  
 2219  
 2220  
 2221  
 2222  
 2223  
 2224  
 2225  
 2226  
 2227  
 2228  
 2229  
 2230  
 2231  
 2232  
 2233  
 2234  
 2235  
 2236  
 2237  
 2238  
 2239  
 2240  
 2241  
 2242  
 2243  
 2244  
 2245  
 2246  
 2247  
 2248  
 2249  
 2250  
 2251  
 2252  
 2253  
 2254  
 2255  
 2256  
 2257  
 2258  
 2259  
 2260  
 2261  
 2262  
 2263  
 2264  
 2265  
 2266  
 2267  
 2268  
 2269  
 2270  
 2271  
 2272  
 2273  
 2274  
 2275  
 2276  
 2277  
 2278  
 2279  
 2280  
 2281  
 2282  
 2283  
 2284  
 2285  
 2286  
 2287  
 2288  
 2289  
 2290  
 2291  
 2292  
 2293  
 2294  
 2295  
 2296  
 2297  
 2298  
 2299  
 2300  
 2301  
 2302  
 2303  
 2304  
 2305  
 2306  
 2307  
 2308  
 2309  
 2310  
 2311  
 2312  
 2313  
 2314  
 2315  
 2316  
 2317  
 2318  
 2319  
 2320  
 2321  
 2322  
 2323  
 2324  
 2325  
 2326  
 2327  
 2328  
 2329  
 2330  
 2331  
 2332  
 2333  
 2334  
 2335  
 2336  
 2337  
 2338  
 2339  
 2340  
 2341  
 2342  
 2343  
 2344  
 2345  
 2346  
 2347  
 2348  
 2349  
 2350  
 2351  
 2352  
 2353  
 2354  
 2355  
 2356  
 2357  
 2358  
 2359